

**P/N: 55904-8123****Copyright**

© 2015, FLIR Systems, Inc.

All rights reserved worldwide. Names and marks appearing herein are either registered trademarks or trademarks of FLIR Systems and/or its subsidiaries. All other trademarks, trade names or company names referenced herein are used for identification only and are the property of their respective owners.

**Document identity**

Publ. No.: 55904-8123

Release:

Commit: 24597

Language: en-US

Modified: 2015-04-09

Formatted: 2015-04-09

**Corporate Headquarters**

FLIR Systems, Inc.

27700 SW Parkway Ave.

Wilsonville, OR 97070

USA

Telephone: +1-503-498-3547

**Website**

<http://www.flir.com>

**Customer support**

<http://support.flir.com>

**Disclaimer**

Specifications subject to change without further notice. Camera models and accessories subject to regional market considerations. License procedures may apply. Products described herein may be subject to US Export Regulations. Please refer to [exportquestions@flir.com](mailto:exportquestions@flir.com) with any questions.

**General description**

The FLIR T630sc is designed for the expert requiring the highest performance and the latest technology available. The camera combines excellent ergonomics and feature-rich flexibility with superior image quality of 640 x 480 pixel infrared resolution. High accuracy and sensitivity together with streaming options make the FLIR T630sc well suited for advanced research and development.

**Benefits:**

- Tailor made for research and development: The FLIR T630sc has high accuracy and high sensitivity to accurately measure the smallest temperature differences.
- Flexible and feature rich: A wide variety of measuring and analysis functions makes the camera flexible and able to meet your every need. A programmable button provides easy access to favorite functions.
- Highest performance with the latest technology: The FLIR T630sc is equipped with the innovative Multi Spectral Dynamic Imaging (MSX) feature, which produces an image richer in detail than ever before. Continuous auto-focus makes the FLIR T630sc the first fully automatic infrared camera on the market.
- Extensive communication options: The Wi-Fi connectivity of the FLIR T630sc allows you to connect to smart phones or tablets for the wireless transfer of images or the remote control of the camera. The Bluetooth-based METERLINK function transfers readings from external measurement instruments to the infrared image.
- Support for UltraMax: When enabling UltraMax in the camera, the resolution of images can be substantially enhanced when importing the images into FLIR Tools.

**Imaging and optical data**

IR resolution	640 x 480 pixels
UltraMax	Yes
Thermal sensitivity/NETD	<30 mK @ +30°C (+86°F)
Field of view (FOV)	25° x 19°
Minimum focus distance	0.25 m (0.82 ft.)
Focal length	25 mm (0.97 in.)
Spatial resolution (IFOV)	0.68 mrad
Lens identification	Automatic
F-number	1.0
Image frequency	30 Hz
Focus	Automatic (one shot) or manual

P/N: 55904-8123

© 2015, FLIR Systems, Inc.  
#55904-8123; r. /24597; en-US

Imaging and optical data	
Digital zoom	1–4x continuous
Digital image enhancement	Adaptive digital noise reduction
Detector data	
Detector type	Focal plane array (FPA), uncooled microbolometer
Spectral range	7.5–14 µm
Detector pitch	17 µm
Image presentation	
Display	Built-in touch screen, 4.3 in. wide screen LCD, 800 × 480 pixels
Display type	Capacitive touch screen
Auto orientation	Automatic landscape or portrait
Automatic image adjustment	Continuous, histogram based
Manual image adjustment	Linear based; possible to adjust level/span/max./min.
Image presentation modes	
Infrared image	Full-color IR image
Visual image	Full color visual image
Thermal MSX	Thermal image with enhanced detail presentation
Picture in Picture	Resizable and movable IR area on visual image
Measurement	
Object temperature range	<ul style="list-style-type: none"> <li>-40°C to +150°C (-40°F to +302°F)</li> <li>+100°C to +650°C (+212°F to +1202°F)</li> </ul>
Accuracy	<ul style="list-style-type: none"> <li>±1°C (±1.8°F) or ±1% of reading for limited temperature range.</li> <li>±2°C (±3.6°F) or 2%, whichever is greater, at 25°C (77°F) nominal.</li> </ul>
Measurement analysis	
Spotmeter	10
Area	5 areas (boxes or circles) with max./min./average
Automatic hot/cold detection	Auto hot or cold spotmeter markers within area
Measurement presets	No measurements, Center spot, Hot spot, Cold spot, User preset 1, User preset 2
User presets	The user can select and combine measurements from any number of spots/boxes/circles/delta
Difference temperature	Delta temperature between measurement functions or reference temperature
Reference temperature	Manually set using difference temperature
Atmospheric transmission correction	Automatic, based on inputs for distance, atmospheric temperature and relative humidity
Optics transmission correction	Automatic, based on signals from internal sensors
Emissivity correction	Variable from 0.01 to 1.0 or selected from materials list
Emissivity table	Emissivity table of predefined materials

P/N: 55904-8123

© 2015, FLIR Systems, Inc.  
#55904-8123; r. /24597; en-US

Measurement analysis	
Reflected apparent temperature correction	Automatic, based on input of reflected temperature
External optics/windows correction	Automatic, based on inputs of window transmission and temperature
Measurement corrections	Emissivity, reflected temperature, relative humidity, atmospheric temperature, object distance, external IR window compensation
Colors (palettes)	Iron, Rainbow, Rainbow HC, White hot, Black hot, Arctic, Lava
Alarm	
Color Alarm (isotherm)	Above/below/interval
Measurement function alarm	Audible/visual alarms (above/below) on any selected measurement function
Screening	Difference temperature alarm, audible
Set-up	
Set-up commands	Define user presets, Save options, Programmable button, Reset options, Set up camera, Wi-Fi, GPS & compass, Bluetooth, Language, Time & units, Camera information
Service functions	
Camera software update	Use PC software FLIR Tools
Storage of images	
Image storage	Standard JPEG, including digital photo and measurement data, on memory card
Storage media	Removable memory SD card
Image storage mode	<ul style="list-style-type: none"> <li>Simultaneous storage of thermal and digital photo in same JPEG file.</li> <li>Optional to store digital photo as a separate JPEG file.</li> </ul>
Time lapse	15 seconds to 24 hours
File formats	Standard JPEG, measurement data included
File formats, visual	Standard JPEG, automatically associated with corresponding thermal image
Image annotations (in still images)	
Voice	60 seconds (via Bluetooth) stored with the image
Text	Add table. Select between predefined templates or create your own in FLIR Tools
Image description	Add short note (stored in JPEG EXIF tag)
Sketch	Draw on thermal/digital photo or add predefined stamps
METERLINK	Wireless connection (Bluetooth) to: FLIR meters with METERLINK
Report generation	<ul style="list-style-type: none"> <li>Instant Report (*.pdf file) in camera</li> <li>Separate PC software with extensive report generation</li> </ul>

P/N: 55904-8123

© 2015, FLIR Systems, Inc.  
#55904-8123; r. /24597; en-US

Geographic Information System	
GPS	Location data automatically added to every still image from built-in GPS
Compass	Camera direction automatically added to every still image
Video recording in camera	
Non-radiometric IR video recording	MPEG-4 to memory card
Visual video recording	MPEG-4 to memory card
Video streaming	
Radiometric IR video streaming	Full dynamic to PC using USB or to mobile devices using Wi-Fi.
Non-radiometric IR video streaming	<ul style="list-style-type: none"> <li>• MPEG-4 using Wi-Fi</li> <li>• Uncompressed colorized video using USB</li> </ul>
Visual video streaming	<ul style="list-style-type: none"> <li>• MPEG-4 using Wi-Fi</li> <li>• Uncompressed colorized video using USB</li> </ul>
Digital camera	
Built-in digital camera	5 Mpixels with LED light (photo as separate image)
Digital camera, FOV	Adapts to the IR lens
Video lamp	Built-in LED light
Laser pointer	
Laser	Activated by dedicated button
Laser alignment	Position is automatic displayed on the IR image
Laser classification	Class 2
Laser type	Semiconductor AlGaInP diode laser, 1 mW, 635 nm (red)
Data communication interfaces	
Interfaces	USB-mini, USB-A, Bluetooth, Wi-Fi, Digital Video Output
METERLiNK/Bluetooth	Communication with headset and external sensors
Wi-Fi	Peer to peer (ad hoc) or infrastructure (network)
SD Card	One card slot for removable SD memory cards
USB	
USB	<ul style="list-style-type: none"> <li>• USB-A: Connect external USB device</li> <li>• USB Mini-B: Data transfer to and from PC / uncompressed colorized video</li> </ul>
USB, standard	USB 2.0 high speed
Video output	
Video out	Digital video output (DVI)
Video, connector type	HDMI compatible



## FLIR T630sc 25° (incl. Wi-Fi)

P/N: 55904-8123

© 2015, FLIR Systems, Inc.  
#55904-8123; r. /24597; en-US

Radio	
Wi-Fi	<ul style="list-style-type: none"><li>Standard: 802.11 b/g</li><li>Frequency range: 2412–2462 MHz</li><li>Max. output power: 15 dBm</li></ul>
METERLiNK/Bluetooth	Frequency range: 2402–2480 MHz
Antenna	Internal
Power system	
Battery type	Rechargeable Li ion battery
Battery operating time	> 2.5 hours at 25°C (+68°F) and typical use
Charging system	In camera (AC adapter or 12 V from a vehicle) or 2-bay charger
Charging time	2.5 h to 90 % capacity, charging status indicated by LED's
Charging temperature	0°C to +45°C (+32°F to +113°F)
External power operation	AC adapter 90–260 VAC, 50/60 Hz or 12 V from a vehicle (cable with standard plug, optional)
Environmental data	
Operating temperature range	-15°C to +50°C (+5°F to +122°F)
Storage temperature range	-40°C to +70°C (-40°F to +158°F)
Humidity (operating and storage)	IEC 60068-2-30/24 h 95% relative humidity +25°C to +40°C (+77°F to +104°F) / 2 cycles
EMC	<ul style="list-style-type: none"><li>ETSI EN 301 489-1 (radio)</li><li>ETSI EN 301 489-17</li><li>EN 61000-6-2 (Immunity)</li><li>EN 61000-6-3 (Emission)</li><li>FCC 47 CFR Part 15 Class B (Emission)</li><li>ICES-003</li></ul>
Radio spectrum	<ul style="list-style-type: none"><li>ETSI EN 300 328</li><li>FCC Part 15.247</li><li>RSS-210</li></ul>
Encapsulation	IP 54 (IEC 60529)
Shock	25 g (IEC 60068-2-27)
Vibration	2 g (IEC 60068-2-6)
Safety	EN/UL/CSA/PSE 60950-1
Physical data	
Weight	1.3 kg (2.87 lb.)
Camera size, excl. lens (L × W × H)	143 × 195 × 95 mm (5.6 × 7.7 × 3.7 in.)
Tripod mounting	UNC 1/4"-20
Housing material	Magnesium

P/N: 55904-8123

© 2015, FLIR Systems, Inc.  
#55904-8123; r. /24597; en-US

Shipping information	
Packaging, type	Cardboard box
List of contents	<ul style="list-style-type: none"> <li>• Infrared camera with lens</li> <li>• Battery (2 ea.)</li> <li>• Battery charger</li> <li>• Bluetooth headset</li> <li>• Calibration certificate</li> <li>• FLIR ResearchIR Max 4</li> <li>• FLIR Tools download card</li> <li>• User documentation CD-ROM</li> <li>• Printed documentation</li> <li>• HDMI-DVI cable</li> <li>• HDMI-HDMI cable</li> <li>• Hard transport case</li> <li>• Lens cap</li> <li>• Memory card</li> <li>• Neck strap</li> <li>• Power supply, incl. multi-plugs</li> <li>• Tripod adapter</li> <li>• USB cable, Std A to Mini-B</li> </ul>
Packaging, weight	6.6 kg (14.6 lb.)
Packaging, size	495 × 192 × 370 mm (19.49 × 7.56 × 14.57 in.)
EAN-13	7332558008713
UPC-12	845188009236
Country of origin	Sweden

## Supplies & accessories:

- T197914; IR lens, f=41.3 mm (15°) with case
- T197922; IR lens, f=24.6 mm (25°) with case
- T197915; IR lens, f=13.1 mm (45°) with case
- T198059; Close-up IR lens, 2.9x (50 µm) with case
- T198060; Close-up IR lens, 5.8x (100 µm) with case
- T198166; IR lens, f=88.9 mm (7°) with case and support for T6xx
- T198065; IR lens, f=6.5 mm (80°) with case
- T198066; Close-up IR lens, 1.5x (25 µm) with case
- T197896; High temp option +300°C to 2000°C (+572°F to 3632°F) for FLIR A6xxsc and T6xx
- T910814; Power supply, incl. multi plugs
- T198126; Battery charger, incl. power supply with multi plugs T6xx
- T198506; Li-Ion Battery pack 3.7V 29Wh
- T911230ACC; Memory card SDHC 4 GB
- 1910423; USB cable Std A <> Mini-B
- T198509; Cigarette lighter adapter kit, 12 VDC, 1.2 m/3.9 ft.
- T910930ACC; HDMI type C to DVI cable 1.5 m
- T910891ACC; HDMI type C to HDMI type A cable 1.5 m
- T198625ACC; Hard transport case for T6xx series
- T198495; Pouch for FLIR T6xx and T4xx series
- T198497; Large eyecup
- T198498; Tripod Adapter
- T198499; Neck strap
- T197771ACC; Bluetooth Headset
- T911093; Tool belt
- 19250-100; IR Window 2 in.
- 19251-100; IR Window 3 in.
- 19252-100; IR Window 4 in.
- 19250-200; SS IR Window 2 in.
- 19251-200; SS IR Window 3 in.
- 19252-200; SS IR Window 4 in.
- T198586; FLIR Reporter Professional (license only)



## FLIR T630sc 25° (incl. Wi-Fi)


---

P/N: 55904-8123

© 2015, FLIR Systems, Inc.  
#55904-8123; r. /24597; en-US


- T198584; FLIR Tools
- T198583; FLIR Tools+ (license only)
- DSW-10000; FLIR IR Camera Player
- APP-10002; FLIR Tools Mobile (Android Application)
- APP-10004; FLIR Tools (MacOS Application)
- T198697; FLIR ResearchIR Max + HSDR 4
- T199014; FLIR ResearchIR Max + HSDR 4
- T199044; FLIR ResearchIR Max + HSDR 4 Upgrade
- T198696; FLIR ResearchIR Max 4
- T199013; FLIR ResearchIR Max 4
- T199043; FLIR ResearchIR Max 4 Upgrade
- T198731; FLIR ResearchIR Standard 4
- T199012; FLIR ResearchIR Standard 4
- T199042; FLIR ResearchIR Standard 4 Upgrade

Camera housing



Product may be subject to US Export Regulations. Please refer to [exportusolutions.com](#) with any questions. Licensee may apply for a license if it is not covered under the EAR. Sanctions restrictions apply to specific products. Disposition of end items made from or containing restricted material may be restricted under U.S. and local laws and regulations. Licensee is responsible for obtaining necessary export licenses or other authorizations for such items.

# Camera with Lens IR f=6,5 mm (80°)



Product must not be exported to US Export Regulations. Please refer to export regulations@flir.com with any questions. Diversion contrary to US law is prohibited.

© 2012 FLIR Systems, Inc. All rights reserved worldwide. No part of this drawing may be reproduced, stored in a retrieval system, or transmitted in any form, or by any means, electronic, mechanical, photocopying, recording, or otherwise, without written permission from FLIR Systems, Inc. Specifications subject to change without further notice. Lateral resolution data is based on nominal values. Products may be subject to regional market considerations. Localized procedures may apply.

For additional dimensions see page 1







**FLIR**

Sheet 2(9)  
Drawing No. T128123

Basic dimensions FLIR T6xx mk II

Modified 2014-02-18	Check JOT-A	Drawn by R&D Thermography
Denomination		
A3	1,2	Sheet 2(9)
Size A	Scale 1:2	Drawing No. T128123


# Camera with Lens IR f=13,1 mm (45°)



Basic dimensions FLIR T6xx mk II		For additional dimensions see page 1	
Modified 2014-02-18	Check JOTA	Drawn by R&D Thermography	Denomination
Size A3	Scale 1:2	Sheet 3(9)	Drawing No. T128123
Size A	Sheet 3(9)	Size A	

# Camera with Lens IR f=24,6 mm (25°)

10  
9  
8  
7  
6  
5  
4  
3  
2  
1



C

D

E

F

G

A

B

C






D

E

F

G

H



For additional dimensions see page 1

**FLIR**







Sheet 4(9)  
Drawing No. T128123  
Size A

Basic dimensions FLIR T6xx mk II

Modified 2014-02-18 Check JOTA Drawn by R&D Thermography  
Denomination

Size A3	Scale 1:2	Sheet 4(9)
Size A	Sheet 4(9)	Size A

# Camera with Lens IR f=41,3 mm (15°)



For additional dimensions see page 1





FLIR®	
Drawing No.	T128123
Sheet	5(9)
Size	A
Scale	1:2
Denomination	R&D Thermography
Drawn by	R&D Thermography
Check	JOT/A
Modified	2014-02-18

## Basic dimensions FLIR T6xx mk II



1 2 3 4 5 6

1 2 3 4 5 6

# Camera with Lens f=88,9 mm (7°) incl support



Lens support  
Optional



For additional dimensions see page 1

**FLIR**

Sheet 6(9)  
Drawing No. T128123  
Size A


Basic dimensions FLIR T6xx mk II

Denomination

Modified 2014-02-18 Check JOTA Drawn by R&D Thermography

Sheet 6(9)  
Drawing No. T128123  
Size A

# Camera with Close-up lens 1,5X (25 µm)



© 2012 FLIR Systems, Inc. All rights reserved worldwide. No part of this drawing may be reproduced, stored in a retrieval system, or transmitted in any form, or by any means, electronic, mechanical, photocopying, recording, or otherwise, without written permission from FLIR Systems, Inc. Specifications subject to change without further notice. International data is based on nominal values. Products may be subject to regional market considerations. Licensee procedures may apply. Product must be shipped to US Export Regulations. Please refer to export regulations@flir.com with any questions. Deviations contrary to US law is prohibited.

For additional dimensions see page 1

**FLIR**


Sheet 7(9)
Drawing No. T128123
Size A
Size A3

Scale 1:2
Denomination
Modified 2014-02-18

Check JOTA
Drawn by R&D Thermography
Denomination

Page 1
--------

# Camera with Close-up lens 2,9X (50 µm)



For additional dimensions see page 1

**FLIR**

Sheet 8(9)  
Drawing No. T128123  
Size A

Size A  
Scale 1:2  
Denomination


Basic dimensions FLIR T6xx mk II

Modified 2014-02-18 Check JOTA Drawn by R&D Thermography

Denomination

Product must be subject to US Export Regulations. Please refer to exportregulations@flir.com with any questions. Deviations contrary to US law is prohibited.  
©2012 FLIR Systems, Inc. All rights reserved worldwide. No part of this drawing may be reproduced, stored in a retrieval system, or transmitted in any form, or by any means, electronic, mechanical, photocopying, recording, or otherwise, without permission from FLIR Systems, Inc. Specifications subject to change without notice. Dimensional data is based on nominal values. Products may be subject to regional market considerations. Local procedures may apply.

# Camera with Close-up lens 5,8X (100 μm)



Product must not be exported to US Export Regulations. Please refer to export regulations@flir.com with any questions. Disclosure contrary to US law is prohibited.  
©2012 FLIR Systems, Inc. All rights reserved worldwide. No part of this drawing may be reproduced, stored in a retrieval system, or transmitted in any form, or by any means, electronic, mechanical, photocopying, recording, or otherwise, without written permission from FLIR Systems, Inc. Specifications subject to change without further notice. Dimensional data is based on nominal values. Products may be subject to regional market considerations. Localized procedures may apply.

For additional dimensions see page 1

FLIR®	
Drawing No.	T128123
Scale	1:2
Size	A3
Sheet	9(9)
Denomination	

Basic dimensions FLIR T6xx mk II

Modified	2014-02-18	Check	JOTA	Drawn by	R&D Thermography
----------	------------	-------	------	----------	------------------

1



March 25, 2013

AQ125879B

## CE Declaration of Conformity

This is to certify that the System listed below have been designed and manufactured to meet the requirements, as applicable, of the following EU-Directives and corresponding harmonising standards. The systems consequently meet the requirements for the CE-mark.

### Directives:

- Directive 2004/108/EC;** **Electromagnetic Compatibility**  
**Directive 2006/95/EC;** **“Low voltage Directive” (Power Supply)**  
**Directive 1999/5/EC** **“R&TTE on radio equipment and telecommunications terminal equipment”**  
**Directive 2002/96/EC** **Waste electrical and electronic equipment; WEEE**  
(As applicable)

### Standards:

- Emission:** **EN 61000-6-3; Electro magnetic Compatibility Generic standards - Emission**  
**Immunity:** **EN 61000-6-2; Electro magnetic Compatibility; Generic standards - Immunity**  
**Safety (Power Supply):** **EN 60950; (or other)**  
**Safety of information technology equipment**  
**Radio** **ETSI EN 301489**  
**System:** **FLIR T6xx series**

FLIR Systems AB  
Quality Assurance

Björn Svensson  
Director